

OzLine 12CS

12-Channel Remote Video Digital Dialer

Specifications.....



Features

- New video services
- False alarm verification
- Easy to install
- IP networking not required
- Transmits images over standard or cellular phone lines
- Remote control of external devices
- Fully integrated with most central station automation software
- Higher and constant streaming video quality over any bandwidth
- Supported by monitoring stations all over the world

UNIT

- Measures: 112" x 118" x 31" (285mm x 300mm x 80mm)
- Weight: 6.6lbs (3 kg)
- Power source requires 12 to 17 VDC input 1 amp (not included)
- Operating temperature: 32°-131 °F (0°-50° C)
- Wall mount

VIDEO

- 12 video inputs (75 W 1 Vp-p)
- Loop through for all video inputs
- Works with most existing CCTV equipment
- Transmission rate of up to 10FPS (frames per second)
- Video quality is user defined
- One video out (75 W 1 Vp-p) with built-in sequential switcher for on-site monitoring
- Video resolution: 512 x 200, 256 x 200, 256 x 100, 128 x 100 (NTSC or PAL)

ALARM INPUTS AND ACTIVATION OUTPUTS

- 16 alarm inputs (dry contacts NO/NC)
- Arm/disarm state controlled locally or remotely
- 3 activation outputs for external devices such as lights and doors (dry contact outputs 2A at 24VDC)
- Unit can be configured to allocate an activation output to any alarm input and/or self-testing event.
- Record pre and post video from a selected zone
- Automatic dialing to monitoring station with pre and post trigger

COMMUNICATIONS

- Built-in 56K modem
- Built-in RS232 port to be connected to a local PC and peripheral systems
- Video transmission over standard public networks such as PSTN, Cellular (GSM and CDMA), ISDN and WAN/LAN (optional communication adaptor may be needed)
- Answering machine/fax defeat

ADDITIONAL SPECIFICATIONS

- Control PTZ domes and cameras with optional kit (specific protocols are supported)
- Capable of transmitting video to a Pocket PC PDA (software is required, supported by specific models)
- Call back feature for reversing phone charges
- 7.5MB of memory available for on-site video recording of events and storage of up to 1000 frames

VIEWER SOFTWARE

- Viewing software included (compatible with Windows 98/NT/2000/Me/XP)



OzVision Corporate Headquarters
400 West Cummings Park
Woburn, MA 01801

Tel: 1 800 385-2317, Intl. Tel: +1 781-932-6900
www.ozvision.com